

LAMINATOR



SPEED OVERVIEW

foil thickness	speed
2 x 75 mic	approx. 2000 mm
2 x 100 mic	approx. 1300 mm
2 x 125 mic	approx. 1000 mm
2 x 175 mic	approx. 650 mm
2 x 250 mic	approx. 540 mm

**HIGH
SPEED**

**ANTI JAM
DETECTION**

**AUTOMATIC
POUCH
DETECTION**

RECOsystems RECO LAM 326

laminator for laminating pouches (A3)

The RECOsystems RECO LAM 326 is a very popular machine for office, copyshop or print houses. The machine is ready one minute after switching it on. It can laminate pouches with thicknesses from 2x75 - 2x250 mic. The temperature is constant but the speed level changes if you change the pouch thickness. For pouches with 2x75 mic. the speed is about 2000 mm/min. If the pouches are thicker, the speed gets slower. The machine has an auto thickness detection. This means the machine adjusts itself automatically depending on the pouch thickness you use. This makes the laminating very easy. If you wish you can also adjust the machine yourself.

Beside that the machine has an anti jam detection, so the machine reverses automatically if a possible jam is detected.

technical specifications:

- working width: A3, 320 mm
- pouch thickness: 2 x 75 - 2 x 250 mic
- max. total laminating thickness: 1 mm
- speed: 2000 mm/min at 75 mic
(the thicker the pouch, the slower the speed)
- heating up time: 1 min
- temperature constant, speed depends on pouch thickness
- reverse function
- automatic switch off function
- automatic detection of pouch thickness
- 6 rollers
- 1750 W
- 230V, 50 Hz
- weight: 6,2/ 5,5 kg
- dimensions: 600x180x240 mm / 520x370x130 mm *

*packing size/machine size (width x depth x height)