

RENZ

Premium Quality



WIRE|GO 3:1 und WIRE|GO 2:1


- Recognized and proven ergonomic two-lever system
- High quality, low force punching for up to 20 sheets per punching operation
- Binds up to 135 sheets (*WIRE GO 3:1*) and 280 sheets (*WIRE GO 2:1*)
- Integrated wire comb holding device for easy loading of punched sheets
- Quick diameter adjustment by means of slider
- Cover with integrated measurement ruler for wire comb diameter
- Fixed margin depth
- Adjustable paper stop
- Large punching waste tray
- Compact and space-saving
- Extremely robust metal construction (15 kg)

TECHNICAL DATA IN DETAIL

Function / Feature	WIRE GO 3:1	WIRE GO 2:1
Binding element Ø	3/16" to 5/8" (5,5 bis 16,0 mm)	1/4" to 1 1/4" (6,9 bis 32 mm)
Max. binding width	300 mm	300 mm
Number of punch pins	34	23
Loops	A4 = 34 / A5 = 24	A4 = 23 / A5 = 16
Machine dimensions	190x333x456mm	190x333x456mm
Machine weight	15,4 kg	15,4 kg
Selectable punch pins (QSA)	No	No
Max. punching thickness	Up to 2,0 mm (20 sheets)	Up to 2,0 mm (20 sheets)
Adjustable punching depth	fixed	fixed
Max. punching width	300 mm	300 mm
Variable margin depth	yes	yes
Max. Binding thickness	13,5 mm / ca. 135 sheets	28 mm / ca. 280 sheets


All performance outputs are based on 70 - 80 gsm paper

3:1 Pitch



Punch pattern: 4 x 4 mm
3 holes per inch
34 loops in DIN A4
24 loops in DIN A5

2:1 Pitch



Punch pattern: 4 x 4 mm
2 holes per inch
23 loops in DIN A4
16 loops in DIN A5

DUAL II www.dual.hr